

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Problem Image Mailbox.**





**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03291223.0

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

THIS PAGE BLANK (USPTO)



Anmeldung Nr:
Application no.: 03291223.0
Demande no:

Anmeldetag:
Date of filing: 23.05.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

ALCATEL
54, rue La Boétie
75008 Paris
FRANCE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Method for creating a protocol-independant manager/agent relationship, in a
Network Management System of a telecommunication network

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)

Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

... 23.05.03 ...

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

H04L12/24

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT RO SE SI SK TR LI

THIS PAGE BLANK (USPTO)

The present invention relates to a method for creating a protocol-independent manager/agent relationship, in a Network Management System of a telecommunication network.

When a manager/agent relationship has to be detailed, the
5 interface and the objects exchanged have to be defined.

This is strictly correlated with the specific model to use: i.e. GDMO for Q3 network, IDL for CORBA, SMI for SNMP, etc. Moreover, in some cases, also the product release has to be taken into account.

Many models at Network Element level generate also different
10 implementations at Network Management level to be able to understand the underlying dialects.

So there is a need to create an automatic model-independent manager/agent relationship, in particular for the use in the Network Management System of a telecommunication network, for application
15 protocols over CORBA.

Known tools exist for transforming SQL database over CMISE or from XML to databases; however they are not optimized for both generic table-oriented databases and network management application protocols over CORBA, because they don't cover the full network
20 management application needs. Hence manual operations are requested, and specific effort is required both for implementation and test phases.

Therefore the main object of the present invention to provide a method for creating an automatic protocol-independent manager/agent
25 relationship, in a Network Management System of a telecommunication network.

The basic idea of the present invention is to create a meta-model (written in XML language) as a result of the application of a generic, protocol-independent interface, named CSG (Corba Strategic Gateway)
30 tool chain.

It permits to have a generic skeleton based on XML (eXtensible Markup Language) as a reference for NM application starting points. This skeleton permits an application to be independent from NE-NM

interface descriptions irrespective of the NE-NM model and version supported.

The skeleton describes the different implementations using unified rules based on the W3 standardized XML commands.

5 (details can be taken directly from the W3 web site - <http://www.w3.org/>).

Through the creation of the CSG generic protocol-independent interface it is possible to reduce the effort needed to manage different NEs and to have a meta-model written in XML.

10 This solution makes it possible to hide the various differences among protocols.

A further advantage of having this meta-model is to have a XML based definition where the NE functionalities are taken into account in order to cover some lacks that can be found into the general-purpose
15 standard models.

These functionalities are mainly the ones defined in the NMD model where the NE specific needs are covered with proprietary definitions.

20 These and further objects are achieved by means of an apparatus and method as described in the attached claims, which are considered an integral part of the present description.

The invention will become fully clear from the following detailed description, given by way of a mere exemplifying and non limiting example, to be read with reference to the attached drawing figures,
25 wherein:

- Figure 1 shows a block diagram of the system in accordance with the invention;
- Figure 2 shows an example of CSG tool usage.

As known, XML is a language with shaping capabilities and can
30 be used to support presentations of the same meaning in different forms. The format is added later by the presentation device, according to its capabilities, while the contents and logical structure is specified in the XML data. The XML language is described for example in

<http://www.w3.org/XML/>. In the following some features of XML language are described.

- XML is for structuring data - Structured data includes spreadsheets, address books, configuration parameters, financial transactions, and technical drawings. XML is a set of rules for designing text formats that let you structure your data. XML is not a programming language, and you don't have to be a programmer to use it or learn it. XML makes it easy for a computer to generate data, read data, and ensure that the data structure is unambiguous. XML avoids common pitfalls in language design: it is extensible, platform-independent, and it supports internationalization and localization. XML is fully Unicode-compliant.

- XML looks a bit like HTML - Like HTML, XML makes use of tags (words bracketed by '<' and '>') and attributes (of the form name="value"). While HTML specifies what each tag and attribute means, and often how the text between them will look in a browser, XML uses the tags only to delimit pieces of data, and leaves the interpretation of the data completely to the application that reads it.

- XML is a family of technologies - The XML family is a growing set of modules that offer useful services to accomplish important and frequently demanded tasks, like the following. Xlink describes a standard way to add hyperlinks to an XML file. XPointer and XFragments are syntaxes in development for pointing to parts of an XML document. An XPointer is a bit like a URL, but instead of pointing to documents on the Web, it points to pieces of data inside an XML file. CSS, the style sheet language, is applicable to XML as it is to HTML. XSL is the advanced language for expressing style sheets. It is based on XSLT, a transformation language used for rearranging, adding and deleting tags and attributes. The DOM is a standard set of function calls for manipulating XML (and HTML) files from a programming language. XML Schemas help developers to precisely define the structures of their own XML-based formats: that is a language to provide means for defining the structure, content and semantics of XML documents; it

also expresses shared vocabularies and allow machines to carry out rules made by people (the rules could involve filtering, collection of information, relationship between different data, etc.). There are several more modules and tools available or under development.

5 - XML is modular - XML allows to define a new document format by combining and reusing other formats. Since two formats developed independently may have elements or attributes with the same name, care must be taken when combining those formats. To eliminate name confusion when combining formats, XML provides a namespace mechanism. XML Schemas is designed to mirror this support for
10 modularity at the level of defining XML document structures, by making it easy to combine two schemas to produce a third which covers a merged document structure.

 According to the invention, the generic, protocol-independent
15 interface, named CSG (Corba Strategic Gateway), is created according to the following general principles.

 First of all, a set of core primitives is identified in the input model. These primitives represent fundamental operations which are common to all management protocols, such as reading and writing attribute
20 values to/from the managed agent. Through these generic primitives, a management application can be written, for the first time, in a protocol-independent way (though of course it remains model-dependent, which will always be true). If another agent with the same model, but different protocol, has to be managed, the management application is ideally not
25 impacted at all.

 Second, a set of "abstraction" primitives are defined. These primitives let the application perform abstract management operations which may have a direct, concrete equivalent primitive in some "rich" protocols but not in other "simpler" ones. An example can be the Action
30 primitive, which is explicitly supported in CMIP but only implicitly supported (i.e. it may only be obtained as side effect of other operations) in SNMP. The abstraction primitives let the management application programmer write code that can assume these operations are practically

available even when the underlying protocol does not support these concepts.

Third, as an option, several sets of optimized, protocol-oriented primitives are identified and transformed into core primitives. The
 5 protocol-oriented primitives can be present in some protocols.

More particularly, with reference to figure 1, the CSG tool receives in input the proprietary interface definitions, for example :

NMD IDL, TL1: proprietary methods;
 IDL: a CORBA method written in IDL language (Interface Data
 10 Language);
 SMI: a method in SNMP protocol;
 GDMO: a method in CMIP language.

The CSG tool analyses them and generates different output files containing different categories of information. These categories of
 15 information are the following:

- XML grammar describing the content of the interface model;
- NMD skeleton for NE specific information;
- DBase independent access rules;
- JAVA source files to provide a typed-based code immediately
 20 available from applications.

The XML meta-model is defined using the CSG tool. This tool receives in input the proprietary interface definitions, analyses them and outputs several files containing different categories of information. These set of information define the meta-language.

25 Hence the tool is able to decompose the input model into atomic objects, semantically meaningful. Afterwards it analyzes each atomic object identifying the relevant attributes and features such as name, syntax, access type, behaviour. As a result, each attribute is translated into output (e.g. XML/JAVA) format and moved in the proper output
 30 file. The number of input files may vary depending on which language has to be translated; while the meta language output files are always the same, so it could happen to have the split of attributes coming from one file into different output files.

The XML meta-language is composed of the following kinds of files:

- XML Model Descriptor** It describes grouping and containment relations between attributes and classes.
- 5 **DTD Schema** This schema describes the datatype of the attributes and their association with classes. It also specifies whether attributes are optional or mandatory, and their default value, if any. It may be used at run time to validate the stream of XML data coming from the agent using a validating XML parser.
- 10 **XML Data Profile** It contains type, access and other additional information in a format suitable for use by the manager for type/access rights checking and for configuring the GUI as appropriate to prevent errors, offering exactly the commands necessary to access the supported features.
- 15 **DB Access rules** It is a repository for identifying the operations that can be applicable to the attribute/object from a data base point of view: for example, read/write and create/delete permissions. It is useful for agent-side programming because such applications like Zero-installation clients have, by definition, no pre-installed database.
- 20 **JAVA Macrofiles** These files provide the Java management application developer with an API layer providing simplified access to model attributes and methods, with access control rules and syntax automatically enforced by construction. For example, no SET method will be generated for attributes with read-only access, whereas action
- 25 methods will be generated with a signature containing all necessary arguments, of the appropriate types, as method parameters.
- NMD Skeleton** This file contains the definitions common to all the Network Elements NEs used by NM to manage the NE itself.

30 The figure 2 shows an example of definition of the meta-model starting from SNMP and CMIP protocols, where the same type of information are coded into SMI (Structure of Management Information) and GDMO.

The ASN1 input is relating to the definition made in the ASN1

(Abstract Syntax Notation) language of complex data structures and is used to define the other protocols into low level rules for the data transmission.

The input protocols are:

```

5  SNMP:    ifType OBJECT-TYPE
                SYNTAX      IANAifType
                MAX-ACCESS   read-only
                STATUS       current
                DESCRIPTION   "....."
10         ::= { ifEntry 3 }

CMIP:        .....

                xxxPACKAGE
                DEFINED AS ".....";
                ATTRIBUTES
15         ifType GET;

                .....

                ifType ATTRIBUTE
                WITH ATTRIBUTE SYNTAX
                ASN1DefinedTypesModule.ifType;
20         REGISTERED AS { m3100Attribute 25 };

ASN1:    ASN1DefinedTypesModule
                .....
                IfType::=INTEGER
                .....

```

25 The output meta-models defined are:

```

XML Grammar:
<?xml version="1.0"?>.....
<!DOCTYPE ifDescription SYSTEM "ifDescription.dtd">
<ifDescription>
30     <name>
                .....
                <name>ifType</name>
                .....

```

<ifDescription>

DTD sch ma:

.....

<!ELEMENT ifEntry #PCDATA>

5 <!AT TLIST ifEntry ifType CDATA#IMPLIED>

.....

XML Data profile:

.....

ifType RO INT "idx by x,y,z"

10

DB Access rules:

.....

ifType RO

.....

15 This model, focused on the management of a generic NE, is used between EML and NML.

The message is defined by one, or more, XML commands.

The NMD part has the purpose to provide some NE family specific procedure, in order to give to the requestor the information in a protocol dependent way; e.g., the address of an interface is the "NSAP" for the
20 Q3 world, "IP address + UDP port" for the SNMP, etc.

It is also evident that the NM does not care about the languages used.

Further implementation details will not be described, as the man
25 skilled in the art is able to carry out the invention starting from the teaching of the above description.

The present invention can be advantageously implemented through a program for computer comprising program coding means for the implementation of one or more steps of the method, when this
30 program is running on a computer. Therefore, it is understood that the scope of protection is extended to such a program for computer and in addition to a computer readable means having a recorded message therein, said computer readable means comprising program coding

means for the implementation of one or more steps of the method, when this program is run on a computer.

Many changes, modifications, variations and other uses and applications of the subject invention will become apparent to those
5 skilled in the art after considering the specification and the accompanying drawings which disclose preferred embodiments thereof. All such changes, modifications, variations and other uses and applications which do not depart from the spirit and scope of the invention are deemed to be covered by this invention.

THIS PAGE BLANK (15870)

Claims

1. Method for creating a protocol-independent manager/agent relationship, in a Network Management System, characterized in that it comprises the following steps:

5 a meta-model is created as a result of a CSG (CORBA Strategy Gateway) tool chain, so as to have a generic skeleton based on XML meta- language as a reference for Network Management application starting points based on:

- a first set of core primitives, representing fundamental operations which are common to all management protocols;
- 10 - a second set of "abstraction" primitives, which let the application perform abstract management operations;

the said CSG tool chain receiving in input specific protocol-dependent interface definitions, analysing them and generating as output different files containing different categories of information.

15 2. Method according to claim 1, characterized in that said generic skeleton based on XML meta- language further comprises a third set of optimized, "protocol-oriented" primitives, identified and transformed into core primitives.

3. Method according to claim 1 or 2, characterized in that said XML meta-language is composed of the following kinds of files:

20 "XML Model Descriptor", describing grouping and containment relations between attributes and classes;

"DTD Schema", describing the datatype of the attributes and their association with classes;

25 "XML Data Profile", containing type, access and other additional information in a format suitable for use by the manager for type/access rights checking and for configuring a Graphical User Interface;

"DB Access rules", a repository identifying the operations that can be applicable to the attribute/object from a data base point of view;

30 "JAVA Macrofiles", files providing the Java management application

developer with an API layer providing simplified access to model attributes and methods, with access control rules and syntax automatically enforced by construction;

5 "NMD Skeleton", a file containing the definitions common to all the Network Elements (NEs) used by the Network Management to manage the NEs.

4. Network Management System of a telecommunication network characterized in that it comprises means for implementing the method of any of claims 1 to 3.

10 5. Computer program comprising computer program code means adapted to perform all the steps of claim 1 to 3. when said program is run on a computer.


6. A computer readable medium having a program recorded thereon, said computer readable medium comprising computer program code
15 means adapted to perform all the steps of claim 1 to 3 when said program is run on a computer.

Abstract

Method for creating a protocol-independent manager/agent relationship, in a Network Management System of a telecommunication network.

The present invention relates to a method for creating a protocol-independent manager/agent relationship, in a Network Management System of a telecommunication network. This is achieved by means of the creation of a meta-model as a result of CSG (CORBA Strategy Gateway) tool chain. It permits to have a generic skeleton based on XML (eXtensible Markup Language) as a reference for NM application starting points. This skeleton permits an application to be independent from NE-NM interface descriptions irrespective of the NE-NM model and version supported. The skeleton describes the different implementations using unified rules based on the W3 standardized XML commands.

THIS PAGE BLANK (USPTO)

FIG. 1




FIG. 2